


TELECOM RANGE



Model No. TEL 30 (12 Volts, 27.6 Ah at 8 hour Rate to 1.75 vpc)
Valve Regulated Lead Acid Battery for communications
standby power applications

Innovative Features

- ◆ Completely maintenance free, sealed construction eliminates the need for watering
- ◆ Fully tank formed plates
- ◆ Analytical Grade electrolyte
- ◆ Spill proof / leak proof
- ◆ Valve regulated Max internal pressure 2.5 psi
- ◆ Multi-position usage
- ◆ ABS Case & Cover Flame Retardant meets UL 94 VO requirements
- ◆ Low self discharge
- ◆ FAA and IATA approved as non-hazardous
- ◆ Designed to comply with Bellcore TR-NWT-000766, Bellcore TR-NWT-000909, ANSI T1.330-1997, Telcordia SR 4228, British Standard BS 6290 Part 4, IEC 896 Part 2, Eurobat, DIN 43534
- ◆ UL Recognized, ISO 9001

Ampere Hour Capacity at 77°F (25°C) to 1.75 vpc

Discharge Time in Hrs	1	2	3	4	5	6	7	8	10
Ampere Hour Capacity	20.7	22.2	23.3	24.2	25.2	26.1	26.9	27.6	28.8

Website: www.hazebattery.com/usa
E mail : customerservice@hazebattery.com
Ph: 952-746-7528 Fax: 952-746-7527



AGM Range
Sealed Lead Acid 12 Volt Bloc

Specifications


Nominal Voltage		12V	
Nominal Capacity		32.5 Ah	
Dimensions	Total Height (Inc terminals)	6.30 inches	160 mm
	Length	n/a	n/a
	Width	7.68 inches	195 mm
	Weight	5.12 inches	130 mm
		24.09 lbs	10.9 Kg



Haze Battery Company Ltd

Characteristics

Capacity 77°F (25°C) to 1.75 vpc	20 hour rate	32.5 Ah
	10 hour rate	28.8 Ah
	5 hour rate	25.2 Ah
	2 hour rate	22.2 Ah
	1 hour rate	20.7 Ah
	Internal Resistance	8.5 mOhms
Capacity correction for temperature Variations (C20)	104°F (40°C)	102%
	68°F (20°C)	100%
	32°F (0°C)	85%
	5°F (-15°C)	65%
Self Discharge 77°F (25°C)	Capacity after 1 month storage	98%
	Capacity after 3 months storage	94%
	Capacity after 6 months storage	86%
Short Circuit Current 77°F (25°C)	1100	
Terminal	Standard	14mm Insert M6 thread
Charging (Constant Voltage)	Float	2.27 - 2.30 vpc (59 - 77°F)



End V per Cell	Ampere Hour at 77°F (25°C)									
	1 hr	2 hr	3 hr	4 hr	5 hr	8 hr	10 hr	12 hr	20 hr	
1.85	19.9	21.4	22.3	23.3	24.2	26.6	27.8	28.8	31.5	
1.80	20.4	21.9	22.9	23.9	24.8	27.2	28.5	29.5	32.2	
1.75	20.7	22.2	23.3	24.2	25.2	27.6	28.8	29.8	32.5	
1.70	21.0	22.6	23.6	24.6	25.5	28.1	29.3	30.4	33.1	


Constant Amps Discharge - Amps at 77°F (25°C)										
1.85	19.90	10.70	7.45	5.82	4.84	3.33	2.78	2.40	1.57	
1.80	20.40	11.00	7.63	5.97	4.95	3.40	2.85	2.46	1.61	
1.75	20.70	11.10	7.76	6.05	5.03	3.45	2.88	2.48	1.63	

Specifications

Design Life	12 Years
Operating Temperature	-4 °F to 122 °F
Grid alloy	Calcium / Tin lead alloy
Plates	Flat Pasted
Separator	Absorbant Glass Mat
Active material	Very high purity lead
Charge Voltage	Float 2.25 - 2.30 VPC @77 °F Cycling 2.35 @77 °F Max. 2.4 VPC Max ripple 0.05C (A)
Electrolyte	Sulphuric acid Analytical grade purity
Venting Valve	EPDM Rubber 1.5 to 2 psi (10.5 - 14 KPa) release pressure. Resealing at 1 psi (7 KPa)
Torque setting	The recommended torque value for all types is 44-62 inch-pounds

Terminal Details

Insert are made from brass with copper, nickel and silver plating giving excellent mechanical, electrical and corrosion resistant properties.



Haze Battery Company keenly encourages environmental awareness; PLEASE follow guidelines for the recycling /disposal of lead.

