

Model 3200 Series Wet Bench Flame Detector

The various chemical vapors, acids and bases used in the semiconductor manufacturing wet benches pose a high potential for costly fires. Fires may result in costly damage to equipment, inventory and clean room facilities. Personnel injury and costly business interruptions are also likely. Factory Mutual requires electro-optical flame detectors in the semiconductor wet benches to monitor for fire. These flame detectors must be suitable for the hostile chemicals used in the etching process (such as hydrofluoric, sulfuric, and hydrochloric acids). Furthermore, they must be tested and approved for fire response to FR polypropylene now used in the construction of wet benches as well as other fuels such as isopropyl alcohol.


The Model 3200 easily adapts to most standard fire extinguishing systems and wet bench systems. It utilizes relay output for alarm and trouble and does not require special controllers or wiring / junction boxes.

The Model 3200 Flame Detector uses proven, stable UV/IR technology to continuously monitor for flame in wet bench applications. Using state-of-the-art micro-processor controlled fire algorithms, the Model 3200 can recognize different types of flame signatures while




rejecting common false alarms. Continuous self diagnostics perform tests of the detector operation. Each flame detector is tested to respond to a 4-inch diameter isopropyl alcohol (IPA) fire at 10 feet with a 120° field of view.

The standard Model 3200 has a sealed polypropylene housing designed to an IEC 529 IP67 rating for protection from a wide variety of acids and solvents. Thus occasional submersion by these chemicals will not damage the detector. The detector is rated over a wide operating temperature range for those applications where drying or heating elements are used. A version utilizing Polyvinylidene Fluoride (PVDF) is also available.



Model 3200 Dimensions



Field of View

Detector Response to Various Fuels			
Fuels	Distance	Fire Size	Response Time
Polypropylene	8 ft.	4 in. dia.	Less than 3 sec.
Isopropyl Alcohol	10 ft.	4 in. dia.	Less than 3 sec.
Heptane	40 ft.	1 sq. ft.	Less than 3 sec.
MEK	15 ft.	4 in. dia.	Less than 3 sec.
Silane	30 ft.	18 in. jet	Less than 3 sec.
Hydrogen	15 ft.	18 in. jet	Less than 3 sec.



Model 3200 Series

Flame Detectors

Specifications

Sensitivity: 3.0 seconds to a 4 inch diameter isopropyl alcohol pan fire (on-axis) @ 10 feet

Field of View: 120° full cone

False Alarm Immunity: Does not alarm to sunlight, fluorescent lights, flashlights, or infrared heaters.

Input Voltage: 12 to 30 volts DC typically 24 VDC

Current Draw: @24 VDC; 28 mA normal mode; 54 mA alarm mode

Operating Range
 Temperature: Operating: 32° to 167°F (0° to 75° C)
 Storage: -40° to 185° F (-40° to 85° C)

Humidity: 10 to 90% RH

Typical Fire Type: FR & HB polypropylene and isopropyl alcohol

Red LEDs: Two, indicating Normal Operation and Trouble/Alarm

Alarm Relay: 1.0 amp @ 30 VDC resistive

Trouble Relay: 1.0 amp @ 30 VDC resistive

UV Sensor: Solar-blind Ultraviolet sensor - radiant energy in the 185 to 260 nm band

IR Sensor: Solid state infrared sensor detecting - IR energy in the .715 to 3.5 microns

Acid/Solvent Resistant Surfaces: Resistant to sulfuric acid, phosphoric acid, hydrofluoric acid, hydrochloric acid, ammonium hydroxide, nitric acid, isopropyl alcohol, deionized water, chromium phosphate, n-methyl-pyrrolidane, organic solvent base photoresist strips, ozone, etc.

Housing: FR Polypropylene (IP67, UL94 flamability rating V0) or (Polyvinylidene Fluoride - PVDF available) (for models -2X and -3X) with a 6 foot pigtail (8 wires standard - 4 wires for the fire relay, 2 wires for the trouble relay and 2 wires fro the power)

Dimensions: 3.4 x 4.2 x 1.0 inches (8.6 x 10.7 x 2.5 cm)

Weight: 1 lb (0.5 Kg)

Approval: FM Approved, CSFM 7210-1608:101

Additional Features

Self-Test Models: Incorporate internal self-test for UV lamp

Enhanced Models: Incorporate internal self-test and a RS-485 computer interface for downloading real time spectral data pre-fire spectral data (includes 2 additional wires in pigtail)

False Alarm and Fire Response				
"This table shows the detectors ability to tolerate both modulated and unmodulated false alarm stimuli and still to detect a fire in the presence of the false alarm source (all fire tests used a 1.75" diameter alcohol pan fire at 6 feet)				
False Alarms Source	Distance	Unmodulated	Modulated	Response Time to Fire
Resistive Electric Heater 1320 Watt	6 Feet	No Response	No Response	Less than 3 sec.
Fluorescent Lights (2) 40 Watt Bulbs	6 Feet	No Response	No Response	Less than 3 sec.
Halogen Light 500 Watt	10 Feet	No Response	No Response	Less than 3 sec.
Incandescent Light 100 Watt	6 Feet	No Response	No Response	Less than 3 sec.

Ordering Information	
3200-01	Standard, (Normally Closed - NC Trouble Relay)
3200-02	Self-test, (NC Trouble Relay)
3200-03	Enhanced, (NC Trouble Relay)
3200-04	Standard, with SealCon and Turk connectors (NC Fire, NC Trouble)
Options:	
3240-01	Flame Detector Tester (for Model 3200 Flame Detector)